

## IN THE CLAIMS

1. (Original) An apparatus for forming a two-dimensional image by light modulation, comprising:

a coherent light source;

a diffuser for diffusing light;

an illumination optical system for irradiating the diffuser with light emitted from the coherent light source;

a diffuser vibration unit for vibrating the diffuser; and

a spatial light modulator disposed near the diffuser, said modulator modulating the light that is emitted from the coherent light source and diffused by the diffuser;

wherein said diffuser vibration unit vibrates the diffuser at a velocity that satisfies an expression,

$$V > dx30 \text{ (millimeters/sec)}$$

which is established between the grain size  $d$  of the diffuser and the velocity  $V$  for vibrating the diffuser.

2. (Original) An apparatus for forming a two-dimensional image by light modulation, comprising:

a coherent light source;

a diffuser for diffusing light;

an illumination optical system for irradiating the diffuser with light emitted from the coherent light source;

a spatial light modulator disposed near the diffuser, said modulator modulating the light that is emitted from the coherent light source and diffused by the diffuser; and

a projector lens for projecting an image which is obtained by light modulation by the spatial light modulator, on a certain plane in space;

wherein a diffusion angle of the diffuser is determined on the basis of a substantial numerical aperture of the illumination optical system, and a brightness of the projector lens.

3. (Original) A two-dimensional image formation apparatus as defined in Claim 2 wherein a relationship,

$$\theta/2 + \sin^{-1}(NA_{in}) < 2 \times \tan^{-1}(1/2f)$$

is established among the diffusion angle  $\theta$  of the diffuser, the substantial numerical aperture  $NA_{in}$  of the illumination optical system, and the brightness  $f$  of the projector lens.

4. (Original) An apparatus for forming a two-dimensional image by light modulation, comprising:

a coherent light source;

a diffuser for diffusing light;

an illumination optical system for irradiating the diffuser with light emitted from the coherent light source;

a spatial light modulator disposed near the diffuser, said modulator modulating the light that is emitted from the coherent light source and diffused by the diffuser; and

a projector lens for projecting an image that is obtained by light modulation by the spatial light modulator, on a certain plane in space;

wherein the spatial light modulator and the diffuser are separated from each other by a distance that is determined on the basis of a diffusion angle of the diffuser, a substantial numerical aperture of the illumination optical system, and a screen size of the spatial light modulator in a diagonal direction.

5. (Original) A two-dimensional image formation apparatus as defined in Claim 4 wherein a relationship,

$$(\theta/2 + \sin^{-1}(NA_{in})) \times L < D/3$$

is established among the diffusion angle  $\theta$  of the diffuser, the substantial numerical aperture  $NA_{in}$  of the illumination optical system, the distance  $L$  between the spatial light modulator and the diffuser, and the screen size  $D$  of the spatial light modulator in the diagonal direction.

6. (Original) An apparatus for forming a two-dimensional image by light modulation, comprising:

a coherent light source;

a diffuser for diffusing light;

an illumination optical system for irradiating the diffuser with light emitted from the coherent light source;

a spatial light modulator disposed near the diffuser, said modulator modulating the light that is emitted from the coherent light source and diffused by the diffuser; and

a projector lens for projecting an image of the spatial light modulator on a certain plane in space;

wherein the spatial light modulator and the diffuser are separated from each other by a distance that is determined on the basis of a pitch of unevenness in the transmissivity of the diffuser, and a substantial numerical aperture of the illumination optical system.

7. (Original) A two-dimensional image formation apparatus as defined in Claim 6 wherein a relationship,

$$L \times NA_{in} > P$$

is established among the pitch  $P$  of unevenness in the transmissivity of the diffuser, the substantial numerical aperture  $NA_{in}$  of the illumination optical system, and the distance  $L$  between the spatial light modulator and the diffuser.

8. (Previously Presented) A two-dimensional image formation apparatus as defined in Claim 1 wherein said illumination optical system includes a light integrator.

9. (Original) A two-dimensional image formation apparatus as defined in Claim 8 wherein said light integrator comprises at least two lens arrays.

10. (Original) A two-dimensional image formation apparatus as defined in Claim 8 wherein said light integrator comprises a rod type light integrator.

11. (Previously Presented) A two-dimensional image formation apparatus as defined in Claim 1 wherein said diffuser comprises a pseudo random diffuser having a surface which is processed so as to obtain a desired diffusion angle.

12. (Original) A two-dimensional image formation apparatus as defined in Claim 11 wherein said pseudo random diffuser is obtained by partitioning a surface of a transparent substrate in a lattice pattern to provide plural cell areas, and processing the cell areas so that adjacent cell areas have different heights.

13. (Original) A two-dimensional image formation apparatus as defined in Claim 12 wherein in said pseudo random diffuser obtained by processing a transparent substrate, a difference in heights between adjacent cell areas is set so that the phases of

light beam passing through these cell areas are shifted by  $\pi/4$  from each other.

14. (Original) A two-dimensional image formation apparatus as defined in Claim 11 wherein said pseudo random diffuser has a concave-convex surface configuration in which the level of the surface thereof varies continuously.

15. (New) A two-dimensional image formation apparatus as defined in Claim 2 wherein said illumination optical system includes a light integrator.

16. (New) A two-dimensional image formation apparatus as defined in Claim 15 wherein said light integrator comprises at least two lens arrays.

17. (New) A two-dimensional image formation apparatus as defined in Claim 15 wherein said light integrator comprises a rod type light integrator.

18. (New) A two-dimensional image formation apparatus as defined in Claim 4 wherein said illumination optical system includes a light integrator.

19. (New) A two-dimensional image formation apparatus as defined in Claim 18 wherein said light integrator comprises at least two lens arrays.

20. (New) A two-dimensional image formation apparatus as defined in Claim 18 wherein said light integrator comprises a rod type light integrator.

21. (New) A two-dimensional image formation apparatus as defined in Claim 6 wherein said illumination optical system includes a light integrator.

22. (New) A two-dimensional image formation apparatus as defined in Claim 21 wherein said light integrator comprises at least two lens arrays.

23. (New) A two-dimensional image formation apparatus as defined in Claim 21 wherein said light integrator comprises a rod type light integrator.

24. (New) A two-dimensional image formation apparatus as defined in Claim 2 wherein said diffuser comprises a pseudo random diffuser having a surface which is processed so as to obtain a desired diffusion angle.

25. (New) A two-dimensional image formation apparatus as defined in Claim 24 wherein said pseudo random diffuser is obtained by partitioning a surface of a transparent substrate in a lattice pattern to provide plural cell areas, and processing the cell areas so that adjacent cell areas have different heights.

26. (New) A two-dimensional image formation apparatus as defined in Claim 25 wherein in said pseudo random diffuser obtained by processing a transparent substrate, a difference in heights between adjacent cell areas is set so that the phases of light beam passing through these cell areas are shifted by  $\pi/4$  from each other.

27. (New) A two-dimensional image formation apparatus as defined in Claim 24 wherein said pseudo random diffuser has a concave-convex surface configuration in which the level of the surface thereof varies continuously.

28. (New) A two-dimensional image formation apparatus as defined in Claim 4 wherein said diffuser comprises a pseudo random diffuser having a surface which is processed so as to obtain a desired diffusion angle.

29. (New) A two-dimensional image formation apparatus as defined in Claim 28 wherein said pseudo random diffuser is obtained by



partitioning a surface of a transparent substrate in a lattice pattern to provide plural cell areas, and processing the cell areas so that adjacent cell areas have different heights.

30. (New) A two-dimensional image formation apparatus as defined in Claim 29 wherein in said pseudo random diffuser obtained by processing a transparent substrate, a difference in heights between adjacent cell areas is set so that the phases of light beam passing through these cell areas are shifted by  $\pi/4$  from each other.

31. (New) A two-dimensional image formation apparatus as defined in Claim 28 wherein said pseudo random diffuser has a concave-convex surface configuration in which the level of the surface thereof varies continuously.

32. (New) A two-dimensional image formation apparatus as defined in Claim 6 wherein said diffuser comprises a pseudo random diffuser having a surface which is processed so as to obtain a desired diffusion angle.

33. (New) A two-dimensional image formation apparatus as defined in Claim 32 wherein said pseudo random diffuser is obtained by partitioning a surface of a transparent substrate in a lattice

pattern to provide plural cell areas, and processing the cell areas so that adjacent cell areas have different heights.

34. (New) A two-dimensional image formation apparatus as defined in Claim 33 wherein in said pseudo random diffuser obtained by processing a transparent substrate, a difference in heights between adjacent cell areas is set so that the phases of light beam passing through these cell areas are shifted by  $\pi/4$  from each other.

35. (New) A two-dimensional image formation apparatus as defined in Claim 32 wherein said pseudo random diffuser has a concave-convex surface configuration in which the level of the surface thereof varies continuously.